

## High Rate LiFe cell List



Model	Typical capacity (mAh)	Minimum Capacity (mAh)	Rated Voltage (V)	Dimensions(mm)		Approx Weight (g)	Max Discharge Current	
				Diameter (±0.1)	Length (±1.0)		Continuous Discharge	Peak Discharge
CY18650LF	1100	1000	3.2	18.5	65	42	15C	20C
CY22430LF	950	900	3.2	22.5	42.8	42	15C	20C
CY22650LF	1600	1500	3.2	22.5	65	60	15C	20C
CY26430LF	1300	1200	3.2	26.5	42.8	50	15C	20C
CY26650LF	2200	2100	3.2	26.5	65	76	15C	20C
CY32600LF	3000	3500	3.2	32.5	60	125	15C	20C
CY32900LF	4500	4400	3.2	32.5	90	188	15C	20C

### Note:

1. Capacity is according to the following conditions: Charge, CC-CV, 0.5C @ 3.65V,5h; Discharge, CC, 0.2C @ 2.0V, 25°C.
2. mPnS battery pack is customized upon your requirements, such as 2p3s, 3p2s etc.
3. Above specifications are subject to change without notice. the final size and performance are according to the specification. More information, please consult Chargery power co.,ltd.

CHARGER Power products are designed and manufactured specially for R/C model, it is inspected and tested according to ISO 9001:2000 and other international standard such as CE, UL. etc..

Make sure to check back frequently as we have many new products to be added shortly. These products, as with all the CHARGER Power product line are sure to offer you the ultimate in performance and value.

CHARGER products include LiPo battery packs, chargers, balancers, adapters and balance chargers - a total power solution family for R/C model.

For chargery charger product, please visit [www.chargery.com](http://www.chargery.com) to download the product list.

Thank you for your interest in Chargery lipo battery!